

(19)



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11)

EP 1 161 088 A2

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:
05.12.2001 Bulletin 2001/49

(51) Int Cl.7: H04N 5/765, H04N 7/173

(21) Application number: 01304469.8

(22) Date of filing: 21.05.2001

(84) Designated Contracting States:
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE TR
Designated Extension States:
AL LT LV MK RO SI

(72) Inventors:
• Nashida, Tatsushi, c/o Sony Corporation
Tokyo 141 (JP)
• Ozaki, Naoto, c/o Sony Corporation
Tokyo 141 (JP)

(30) Priority: 31.05.2000 JP 2000162320

(71) Applicant: SONY CORPORATION
Tokyo 141 (JP)

(74) Representative: Pratt, Richard Wilson et al
D. Young & Co,
21 New Fetter Lane
London EC4A 1DA (GB)

(54) Recording system and recording substitution system

(57) A recording center station (200) includes functions for receiving a broadcast wave and saving or recording received data. In response to a request from each receiving station (100), the recording center station (200) substitutionally records a specified broadcast program and provides a recorded content. There may

be the case where the receiving station cannot record a reserved program independently due to insufficient free space remaining in a recording medium or a recording apparatus failure. In this case, the receiving station can automatically issue a recording substitution request to the recording center station for substitution of the program recording.




FIG.1

Description

Technical Field

[0001] The present invention relates to a system for recording a video content. Embodiments of the present invention concern a program reservation and recording system and a recording substitution system for reserving and recording TV programs which are broadcast as scheduled.

Prior Art

[0002] A television set became one of the necessities of daily life a long time ago. In addition to television sets, a video apparatus for recording broadcast programs has come to be widely used. Recently, a multi-channel approach is developing rapidly along with the introduction of satellite broadcasting and cable television, there is an increasing need for the capability of reserving programs preferred by the audience.

[0003] Conventionally, many storage media for recording TV programs employ the sequential access method such as video tape. Recently, with the development of the digital technology and large-sized hard disc drives (HDDs), HDD-based recording devices have become available. These trends are reported in journals such as, say, "Increasingly marketing devices for recording TV programs on HDDs" (Nikkei Electronics, No. 727, pp. 27-28, 1998) and "Digital recording technology using HDDs available for home use" (Nikkei Electronics, No. 727, pp. 41-46, 1998).

[0004] When a large-size recording medium is used for recording programs, it is possible to record a series of dramas for weeks or a plurality of programs in the same time zone for reservation without needing to know the remaining capacity of the recording medium. By contrast, however, reserving a great number of programs may easily cause unsuccessful recording due to incorrect understanding of the remaining storage capacity.

[0005] It was often the case that a video tape cassette with a sufficient recording capacity is found to be unavailable just before the broadcast time of a program to be recorded; the program is not recorded completely because an available size of the video tape becomes insufficient in the middle of the recording; or the recording fails due to a device malfunction or other unexpected events.

[0006] Especially, a failure to record an intended program causes a disappointing and inconvenient result for the audience.

SUMMARY OF THE INVENTION

[0007] An embodiment of the present invention seeks to provide a program reservation and recording system and a recording substitution system capable of reserving TV programs which are broadcast as scheduled.

[0008] An embodiment of the present invention seeks to provide a program reservation and recording system and a recording substitution system capable of servicing reliability of reserved program recording.

[0009] An embodiment of the present invention seeks to provide a program reservation and recording system and a recording substitution system capable of servicing reserved program recording even if no recording is available due to an insufficient capacity in an audience's recording medium.

[0010] A first aspect of the present invention, provides a recording system for recording and/or reserving a broadcast program, comprising: means for accepting a request to record and/or reserve a broadcast program; storage means for recording a broadcast program; connection means for connecting with an external device; determination means for determining whether it is possible to record a broadcast program requested to be recorded and/or reserved; and means for issuing a recording substitution request to an external device via the connection means in response to a negative result of the determination.

[0011] In the recording system according to the first aspect of the present invention, the determination means may generate a negative result when the remaining size for the storage means is insufficient for a broadcast program request to be recorded or reserved. Alternatively, the determination means may generate a negative result when a failure in the system prevents the broadcast program from being recorded in the storage means.

[0012] A second aspect of the present invention is a recording substitution system for substitutionally recording a broadcast program, comprising: connection means for connecting with an external device; means for receiving a broadcast program; storage means for recording a broadcast program; and recording substitution means for responding to reception of a recording substitution request via the connection means and receiving and recording a corresponding broadcast program in the storage means.

[0013] In the recording substitution system according to the second aspect of the present invention, the recording substitution means may receive recording substitution requests from a plurality of external devices and provide many users with a recording substitution service concurrently or parallel. In this case, it is desirable to record and store broadcast programs corresponding to a requesting origin.

[0014] The recording substitution system may be provided with user information management means for storing user information about each requesting origin. In this case, the recording substitution means may record a broadcast program or provide a recorded content in a format appropriate for a user attribute of the requesting origin. Further, the recording substitution means may obtain advertising information appropriate for a user attribute of the requesting origin via the con-

nection means and insert this information in a recorded program. In this case, it may be preferable to appropriate part of the advertising proceeds to the recording substitution service charge for returning a profit to users.

[0015] The recording substitution system according to the present invention comprises a broadcasting station for providing broadcast services, a receiving station for receiving a broadcast wave, and a recording center station for providing the receiving station with program recording services under certain situations.

[0016] The recording center station includes functions of receiving a broadcast wave and saving or recording received data. The recording center station has functions of receiving a broadcast wave and saving or recording received data. In response to a request from each receiving station, the recording center station can substitutionally record specified broadcast programs and provide recorded contents. For example, there may be the case where the receiving station itself cannot record a reserved program because a recording medium leaves no space for recording or a recording apparatus malfunctions. In this case, the receiving station automatically issues a recording substitution request to the recording center station for substituting the program recording.

[0017] In response to the recording substitution request, the recording center station receives a specified broadcast program and records the relevant broadcast content. In addition, the recording center station stores the recorded content in correspondence with an account of the requesting receiving station or other user identification information. The recording center station may automatically distribute the recorded content to the requesting origin after expiration of a specified period or distribute the recorded content in response to a download request from the requesting origin.

[0018] The recording center station may charge the receiving station for program reservation substitution services, say, at a meter rate corresponding to the recording time. Alternatively, the recording center station may insert advertising information in a recorded content and appropriate part of the advertising proceeds to the recording service charge for a discount.

BRIEF DESCRIPTION OF THE DRAWINGS

[0019] For a better understanding of the present invention, reference will now be made by way of example to the accompanying drawings in which:

FIG. 1 schematically shows a configuration of a recording service system 1 for broadcasting and broadcast programs according to the present invention;

FIG. 2 schematically shows a hardware configuration of a receiving station 100 according to this embodiment;

FIG. 3 schematically shows a hardware configura-

tion of a recording center station 200 according to this embodiment;

FIG. 4 is a chart showing a processing procedure for recording substitution in the recording center station 200;

FIG. 5 illustrates how advertising information is inserted into a recorded program content;

FIG. 6 illustrates how advertising information is inserted into a recorded program content; and

FIG. 7 illustrates how advertising information is inserted into a recorded program content.

DETAILED DESCRIPTION OF ILLUSTRATIVE EMBODIMENTS

[0020] FIG. 1 schematically shows a configuration of an illustrative recording service system 1 for broadcasting and broadcast programs according to the present invention. As shown in this figure, the system 1 comprises a broadcasting station 10, a receiving station 100, and a recording center station 200. The broadcasting station 10 provides broadcasting services. The receiving station 100 receives a broadcast wave for viewing broadcast programs. The recording center station 200 provides the receiving station 100 with program recording services in specific modes.

[0021] One or more broadcasting stations 10 scatter on the ground and provide services of distributing broadcast contents according to a specified schedule (program table). Broadcast contents can be distributed by any means including a surface wave, a satellite wave, a radio wave, and wire broadcasting.

[0022] The receiving station 100 corresponds to an ordinary home for audience. Though FIG. 1 shows one receiving station 100, there are many stations on the ground. Basically, the broadcasting station 10 provides unidirectional communication for data distribution or broadcasting.

[0023] The receiving station 100 includes functions of receiving a broadcast wave, decoding received data and outputting video and audio information, and saving or recording received data. Recording is available in any data format before or after decoding.

[0024] The recording center station 200 connects with one or more receiving stations 100 each other through the intermediation of a wide area network such as Internet or other communication media. When a TCP/IP (Transmission Control Protocol/Internet Protocol) network is used for connection, for example, it is possible to perform requests and responses according to the HTTP (Hyper Text Transfer Protocol) and file or mail transfer operations according to the FTP (File Transfer Protocol) between the receiving station 100 and the recording center station 200.

[0025] The recording center station 200 has functions of receiving a broadcast wave and saving or recording received data. In response to a request from each receiving station 100, the recording center station can

substitutionally record specified broadcast programs and provide recorded contents.

[0026] The recording center station 200 works as a type of content server on the TCP/IP network. It is possible to use a resource identifier in the URL (Uniform Resource Locator) format for specifying the recording center station 200 and a recorded program content publicly presented on this station.

[0027] For example, there may be the case where the receiving station 100 itself cannot record a reserved program because a recording medium leaves no space for recording or a recording apparatus malfunctions. In this case, the receiving station automatically issues a recording substitution request to the recording center station 200 for substituting the program recording. The recording substitution can be an HTTP request in the URL format or a mail format.

[0028] In response to the recording substitution request, the recording center station 200 receives a specified broadcast program and records the relevant broadcast content. In addition, the recording center station stores the recorded content in correspondence with an account of the requesting receiving station 100 or other user identification information. The stored recorded content can be identified with, say, a URL on the network.

[0029] The recording center station 200 may automatically distribute the recorded content to the requesting origin after expiration of a specified period or distribute the recorded content in response to a download request from the requesting origin. The requesting receiving station 100 can specify a content to be recorded using URL and download the recorded content according to the protocol such as HTTP or FTP. The receiving station 100 may request to provide a recorded content by sending a mail message. The recording center station 200 may return the recorded content in an attached file format. Instead of providing recorded contents via a network, the recording center station 200 may distribute these contents by copying them on a CD (Compact Disc) or a DVD (Digital Versatile Disc).

[0030] The recording center station 200 may charge the receiving station 100 for program reservation substitution services, say, at a meter rate corresponding to the recording time. Alternatively, the recording center station may insert advertising information in a recorded content and appropriate part of the advertising proceeds to the recording service charge for a discount. It may be also preferable to replace a commercial message inserted in the broadcast program with an advertising content or insert an advertising content in addition to the commercial message. Further, it may be preferable to analyze the user profile based on the contents of recording-requested programs, select advertising contents most appropriate for the user, and attach the selected advertising contents to a recorded content.

[0031] FIG. 2 schematically shows a hardware configuration of a receiving station 100 according to this embodiment. It is possible to configure the receiving station

100 by integrating it in a television set like a set-top box (STB) installed in an ordinary home.

[0032] In the receiving station 100, the CPU (Central Processing Unit) 11 as a main controller connects with each hardware component via a bus 50 for centrally controlling these components. The following describes each component of the content recording and reproducing system 10.

[0033] A broadcast wave received at an antenna (not shown) is supplied to a tuner 51. The broadcast wave follows a specified format and may include information such as EPG (Electric Program Guide). The broadcast wave can be a surface wave, a satellite wave, wire broadcasting, or a radio wave.

[0034] According to an instruction from the CPU 11, the tuner 51 selects a specified channel's broadcast wave for tuning and outputs reception data to a succeeding demodulator 52. The demodulator 52 demodulates digitally modulated reception data. It is possible to change or enhance the configuration of the tuner 11 depending on whether the transmitted broadcast wave is analog or digital.

[0035] In the case of digital satellite broadcasting, for example, digital data received and demodulated from the broadcast wave is a transport stream comprising AV data compressed with MPEG2 (Moving Picture Experts Group 2) and data broadcasting data. The AV data provides audio and video information constituting a broadcast content itself. The data broadcasting data is attached to the broadcast program itself and includes, say, EPG (Electric Program Guide). The transport stream follows specifications for the "transport layer" in the OSI (Open Systems Interconnection) reference model. For implementing the present invention, AV data is not limited to the MPEG2 format as mentioned above, but may use other formats such as MPEG4, MPEG7, Real System, and Quick Time.

[0036] The decoder 53 analyzes this transport stream and separates it into MPEG2-compressed AV data and data broadcasting data. The decoder further separates MPEG2-compressed realtime AV data into compressed video data and compressed audio data. The decoder reproduces the original video signal from the video data by means of MPEG2 expansion. The decoder decodes the audio data according to PCM (Pulse Code Modulation) and synthesizes this data with an additional sound to generate a reproduction audio signal. The decoder 53 may be locally equipped with memory 54 as a work data storage. The reproduced video signal is displayed on a display 61 via a composer 57. The reproduced audio signal is output to a speaker 62 via a mixer 55. For implementing the present invention, audio data is not limited to the PCM format as mentioned above, but may use other formats such as MPEG AUDIO, Real Audio, and Quick Time.

[0037] The decoder 53 transfers the data broadcasting data separated from the transport stream to the CPU 11 via the bus 50. The CPU 11 can use a specific appli-

cation to process the data broadcasting data and use that data for creating an EPG (Electronic Programming Guide) screen.

[0038] According to a request from the CPU 11, the decoder 53 can transfer an MPEG2 stream before expansion or a program content after expansion to the CPU 11 or other devices such as a video deck 64 and an HDD 17 via the bus 50.

[0039] A user interface control section 56 is a module for processing user input operations. This section is provided with a control button or switch (not shown) for user's direct manual operations or a function for accepting remote operations from a remote controller 60 via an infrared ray (IR). This section may contain a display panel or an LED indicator (not shown) for displaying the current settings.

[0040] The CPU (Central Processing Unit) 11 is a main controller for managing operations of the entire receiving station 10 and can execute various applications on a platform provided from the operating system (OS).

[0041] RAM (Random Access Memory) 12 is write-enabled volatile memory used for loading executable program codes for the CPU 11 and writing work data for an executable program. ROM (Read-Only Memory) 13 is write-protected memory for permanently storing control codes for hardware operations and self-diagnostic or initialization programs executed during a power-on sequence for the content recording and reproducing system 10.

[0042] An IEEE1394 (i-link) interface is a high-speed serial interface capable of sending and receiving data at a rate of several tens of megabytes per second. An IEEE 1394 port can be used for connection with IEEE 1394-compliant external devices in a daisy-chain or tree fashion. IEEE1394-compliant devices include, say, a video deck 64 for recording or reserving broadcast contents.

[0043] A hard disc drive (HDD) 17 is a random-access external storage capable of storing programs and data in specified file formats and provides a large capacity of, say, several tens of gigabytes (or 100 GB or more). The HDD 17 is connected to the bus 50 via a hard disc interface 18. A request from the CPU 11 allows broadcast programs to be saved or recorded in an MPEG2 stream format on the HDD 17.

[0044] During a recording operation, an MPEG2 stream before expansion is transferred from the decoder 53 to the HDD 17. The data transfer method is not limited and can be PIO (program I/O), DMA (Direct Memory Access), and the like. For reproducing a recorded content, the MPEG2 stream is retrieved from the HDD 17 and is transferred to the decoder 53 via the bus 50. In the same manner as the reception, the decoder separates the stream into compressed video data and compressed audio data. After the MPEG2 expansion, the compressed data is restored to original video and audio data for reproduction.

[0045] A graphic processing controller 18 is a dedicat-

ed controller for generating computer screens in accordance with drawing instructions issued from the CPU 11 and provides drawing capabilities equivalent to SVGA (Super Video Graphic Array) or XGA (eXtended Graphic Array). The graphic processing controller 18 can draw, say, GUI operation screens and EPG screens.

[0046] The composer 57 composes two or more screens. Accordingly, it can combine a reproduction video restored by the decoder 54 using the MPEG2 expansion and computer graphics generated by the graphic processing controller 18.

[0047] A communication interface 19 is a peripheral device for connecting the receiving station 100 with an external network such as LAN (Local Area Network). The communication interface is further connected to a wide area network such as Internet via an interconnection device such as a router (not shown).

[0048] The CPU 11 processes a recording or reservation command entered by a user from an operation panel of the remote controller 60 or a U/I control section 56 in the receiving station 100 according to an embodiment of the present invention.

[0049] The HDD 17 or the video deck 64 monitors the remaining capacity in a recording medium. When the remaining capacity is insufficient for recording a specified program during the program recording or reservation, the CPU 11 is notified of an insufficient medium capacity. In response to this notification, the CPU 11 uses the graphic processing controller 18 to generate a dialog screen for warning of an insufficient storage capacity or medium replacement. Further, the composer 57 overlaps the alarm dialog on a program screen being broadcast.

[0050] Even if the alarm dialog is displayed for notifying an insufficient medium capacity, a user may take no action and the reservation time may be reached. Alternatively, a medium may be found to leave an insufficient capacity when the recording time is reached or before the recording starts at a specified time. Further, the HDD 17 or the video deck 64 may malfunction to disable recording. In these cases, the CPU 11 generates a recording substitution request and transfers this request to the recording center station 200 via a wide area network.

[0051] The recording substitution request may be an HTTP request in the URL format or a mail message. Alternatively, it may be preferable to use a telephone call to the recording center station 200 via a public telephone line (not shown). It is desirable to have this request include identification information about a program to be recorded and an account or user for the receiving station 100.

[0052] FIG. 3 schematically shows a hardware configuration of the recording center station 200 according to this embodiment. As shown in this figure, the recording center station 200 comprises a recording substitution control section 201, a reception section 202, a communication interface 203, a user information management section 204, a recording program storage section

205, and a broadcast program storage section 206.

[0053] The reception section 202 selects a broadcast wave generated from the broadcasting station 10 and demodulates received data. More preferably, the reception section 202 can simultaneously select a plurality of broadcast waves (multiple decoding).

[0054] The communication interface 203 is a peripheral device for connecting the recording center station 200 to an external network. Accordingly, the recording center station 200 can receive a recording substitution request from the receiving station 100 via the communication interface 203 or retrieve an advertising content from an advertisement server on the network.

[0055] The recording substitution control section 201 responds to a recording substitution request received via the communication interface 203 and centrally controls operations in the recording center station 200.

[0056] When receiving a recording substitution request from the receiving station 100 associated with a given user, the recording substitution control section 201 first accesses a user information database stored in the user information management section 204. It then checks user's validity (namely, whether the user is already registered for the recording center station 200) or obtains user attribute information such as user's hobbies, tastes, types of preferred advertisement media, and the like.

[0057] The recording substitution control section 201 analyzes the content of the recording substitution request and determines for which broadcast program the user requests the recording substitution. The recording substitution control section receives the corresponding program content via the reception section 202, associates the received content with identification information of the requesting user, and stores that program in the recording program storage section 205.

[0058] When a single recording center station 200 provides many users or receiving stations with recording substitution services, many users may issue recording substitution requests to one broadcast program. In this case, receiving and saving the broadcast program does not necessarily require association with the requesting user identification information. The recording center station 200 may temporarily record all broadcast programs from all receivable broadcasting stations independently of whether a recording substitution request is available. It may be preferable to discard programs for which no recording substitution request was issued thereafter from the recording program storage section 205. It may be also preferable to appropriately discard a program content for which all recording substitution requests have been processed from the recording program storage section 205.

[0059] Further, the recording substitution control section 201 may insert advertising information into a recorded program content. It may be preferable to insert advertising information in a recorded content and appropriate part of the advertising proceeds to the recording

service charge for a discount. It may be also preferable to replace a commercial message inserted in the broadcast program with an advertising content or insert an advertising content in addition to the commercial message. Further, it may be preferable to analyze the user profile based on the contents of recording-requested programs, select advertising contents most appropriate for the user, and attach the selected advertising contents to a recorded content.

[0060] Advertising information is provided from an advertisement server 300, say, on an external network. The recording center station 200 can specify advertising information to be used, say, in a URL (Uniform Resource Locator) format. It may be also preferable to use file transfer or other means for periodically or irregularly providing the recording center station 200 with advertising contents an advertiser wants to promote.

[0061] There can be any forms of distributing program contents substitutionally recorded by the recording center station 200 to the requesting receiving station 100. It may be preferable to use a file transfer via an external network or distribution means such as forwarding by mail and a home delivery service by storing recorded programs on recording media such as CD, DVD, video tapes, and the like. It may be also preferable to distribute recorded contents daily or weekly instead of distributing them in units of recorded programs.

[0062] FIG. 4 is a chart showing a processing procedure for recording substitution in the recording center station 200.

[0063] When accepting a recording reservation from the user, the receiving station 100 checks if a recording medium contains a free area large enough to record the program. This recording medium is equivalent to the hard disc drive 17 or a video tape mounted on the video deck 64.

[0064] When the receiving station 100 determines that the medium leaves no free area large enough to record the reserved program, the receiving station sends a recording substitution request to the recording center station 200.

[0065] The recording substitution request may be transmitted in any forms such as electronic mail, an HTTP request, and a telephone call via a public telephone line. It is more preferable to have this request include requesting user identification information and program identification information for specifying recorded programs.

[0066] When receiving the recording substitution request, the recording center station 200 retrieves the user identification information from the request. The recording center station inquires the user information management section 204 therein whether the user is valid. When the user is determined to be valid, namely authenticated to be provided with recording substitution services, the recording center station retrieves the user attribute information describing user's hobbies and tastes from the user information management section

204. The recording center station further obtains the advertising information appropriate for the user attribute information from the external advertisement server 300.

[0067] When the recording start time is reached, the recording center station 200 records the requested program and stores it in the recording program storage section 205. As mentioned above, however, the recording center station 200 may temporarily record all broadcast programs from all receivable broadcasting stations independently of whether a recording substitution request is available.

[0068] The recording center station 200 establishes correspondence between each program content stored in the recording program storage section 205 and the requesting user. At this time, the recording center station inserts advertising information matching the requesting user's attribute information into the recorded program content.

[0069] The advertising information can be inserted in any forms. For example, the advertising information may replace a commercial message in the program content (see FIG. 5). The advertising information may be inserted before or after a commercial message (see FIG. 6). Alternatively, the advertising information may be inserted independently of commercial messages (see FIG. 7).

[0070] The recorded program content with the advertising information inserted therein is saved in the broadcast program storage section 206 in correspondence with the requesting user identification information. In other words, a broadcast program content is common to users who requested recording substitution of the same program. By contrast, a program content with the advertising information inserted therein is customized for each user attribute.

[0071] Finally, the recording center station 200 distributes the substitutionally recorded program content to the requesting receiving station 100. There can be any forms of distributing program contents. It may be preferable to use a file transfer via an external network or distribution means such as forwarding by mail and a home delivery service by storing recorded programs on recording media such as CD, DVD, video tapes, and the like. It may be also preferable to distribute recorded contents daily or weekly instead of distributing them in units of recorded programs. It is also possible to provide a recording substitution service by means of a telephone and distribute recording media such as video tapes without using a system in which royalties on a copyright are paid to a content owner.

[0072] While there have been described specific illustrative embodiments of the present invention, the present invention is not limited thereto but may be otherwise variously embodied within the scope of the invention.

[0073] In so far as the embodiments of the invention described above are implemented, at least in part, using software-controlled data processing apparatus, it will be

appreciated that a computer program providing such software control and a storage medium by which such a computer program is stored are envisaged as aspects of the present invention.

Claims

1. A recording system for recording and/or reserving a broadcast program, comprising:

means for accepting a request to record and/or reserve a broadcast program;
storage means for recording a broadcast program;
connection means for connecting with an external device;
determination means for determining whether it is possible to record a broadcast program requested to be recorded and/or reserved; and
means for issuing a recording substitution request to an external device via said connection means in response to a negative result of said determination.

2. The recording system according to claim 1, wherein said determination means generates a negative result when a remaining capacity of said storage means is not sufficient for recording a broadcast program requested to be recorded and/or reserved;
3. The recording system according to claim 1, wherein said determination means generates a negative result when a failure in said system prevents a broadcast program from being recorded in said storage means.

4. A recording substitution system for substitutionally recording a broadcast program, comprising:

connection means for connecting with an external device;
means for receiving a broadcast program;
storage means for recording a broadcast program; and
recording substitution means for responding to reception of a recording substitution request via said connection means and receiving and recording a corresponding broadcast program in said storage means.

5. The recording substitution system according to claim 4, wherein said recording substitution means can receive recording substitution requests from a plurality of external devices and records a broadcast program corresponding to a requesting origin.

6. The recording substitution system according to

claim 4 further comprising user information management means for storing user information about each requesting origin; wherein said recording substitution means records a broadcast program in a format appropriate for a user attribute of the requesting origin. 5

7. The recording substitution system according to claim 4 further comprising user information management means for storing user information about each requesting origin, wherein said recording substitution means for obtaining advertising information appropriate for a user attribute of the requesting origin via said connection means and inserting said information in a recorded program. 10 15

20

25

30

35

40

45

50

55




FIG.1




FIG.2




FIG.3




FIG.4




FIG.5




FIG.6





FIG.7



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11) **EP 1 161 088 A3**

(12) **EUROPEAN PATENT APPLICATION**

(88) Date of publication A3:
08.09.2004 Bulletin 2004/37

(51) Int Cl.7: **H04N 5/765, H04N 7/173**

(43) Date of publication A2:
05.12.2001 Bulletin 2001/49

(21) Application number: **01304469.8**

(22) Date of filing: **21.05.2001**

(84) Designated Contracting States:
**AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE TR**
Designated Extension States:
AL LT LV MK RO SI

(72) Inventors:
• **Nashida, Tatsushi, c/o Sony Corporation
Tokyo 141 (JP)**
• **Ozaki, Naoto, c/o Sony Corporation
Tokyo 141 (JP)**

(30) Priority: **31.05.2000 JP 2000162320**

(74) Representative: **Pratt, Richard Wilson et al
D. Young & Co,
21 New Fetter Lane
London EC4A 1DA (GB)**

(54) **Recording system and recording substitution system**

(57) A recording center station (200) includes functions for receiving a broadcast wave and saving or recording received data. In response to a request from each receiving station (100), the recording center station (200) substitutionally records a specified broadcast program and provides a recorded content. There may

be the case where the receiving station cannot record a reserved program independently due to insufficient free space remaining in a recording medium or a recording apparatus failure. In this case, the receiving station can automatically issue a recording substitution request to the recording center station for substitution of the program recording.




FIG.1



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 01 30 4469

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim:	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
Y	EP 0 975 163 A (TOSHIBA VIDEO PRODUCTS JAPAN CO., LTD.) 26 January 2000 (2000-01-26) * paragraph [0017] - paragraph [0025]; figures 1-3 *	1-3	H04N5/765 H04N7/173
X	US 5 751 282 A (GIRARD ET AL) 12 May 1998 (1998-05-12)	4,5	
Y	* column 2, line 66 - column 4, line 24 * * column 7, line 26 - line 56 * * figures 1-3,8 *	1-3,6,7	
Y	WO 00/04706 A (UNITED VIDEO PROPERTIES, INC.) 27 January 2000 (2000-01-27)	6	
A	* page 19, line 4 - page 22, line 9 * * page 30, line 24 - page 36, line 24 * * page 43, line 1 - line 30 * * page 46, line 29 - page 48, line 23 * * page 58, line 19 - page 60, line 15 * * page 66, line 7 - line 31 * * page 72, line 18 - page 74, line 25 * * figures 2,7,14,26 *	1-5	
Y	WO 99/45702 A (PREVUE INTERNATIONAL, INC.) 10 September 1999 (1999-09-10) * page 24, line 12 - page 29, line 10; figures 1,3,16-29 *	7	
A	EP 0 665 551 A (SONY CORPORATION) 2 August 1995 (1995-08-02) * page 12, line 31 - page 13, line 16 * * page 15, line 5 - page 16, line 13 * * figures 1,24,25 *	1-3	
The present search report has been drawn up for all claims			
Place of search Berlin		Date of completion of the search 21 July 2004	Examiner Dudley, C
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document		T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document	

EPO FORM 1503 01/92 (P4/C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 01 30 4469

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

21-07-2004

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
EP 0975163	A	26-01-2000	JP 2000050186 A	18-02-2000
			EP 0975163 A2	26-01-2000
US 5751282	A	12-05-1998	NONE	
WO 0004706	A	27-01-2000	AU 758363 B2	20-03-2003
			AU 4994699 A	07-02-2000
			BR 9912086 A	10-04-2001
			CA 2336870 A1	27-01-2000
			CN 1371573 T	25-09-2002
			EP 1383330 A2	21-01-2004
			EP 1145543 A2	17-10-2001
			JP 2003520458 T	02-07-2003
			TW 561781 B	11-11-2003
			WO 0004706 A2	27-01-2000
			US 2003149988 A1	07-08-2003
WO 9945702	A	10-09-1999	AT 237900 T	15-05-2003
			AT 266293 T	15-05-2004
			AU 765648 B2	25-09-2003
			AU 2879099 A	20-09-1999
			AU 748164 B2	30-05-2002
			AU 3310499 A	20-09-1999
			BR 9909238 A	14-11-2000
			BR 9909241 A	14-11-2000
			CA 2322217 A1	10-09-1999
			CA 2322536 A1	10-09-1999
			CA 2454011 A1	10-09-1999
			CN 1297648 T	30-05-2001
			CN 1298604 T	06-06-2001
			DE 69906954 D1	22-05-2003
			DE 69906954 T2	06-11-2003
			DE 69917008 D1	09-06-2004
			EP 1237367 A1	04-09-2002
			EP 1217832 A1	26-06-2002
			EP 1365582 A1	26-11-2003
			EP 1058999 A1	13-12-2000
			EP 1060617 A1	20-12-2000
			ES 2197627 T3	01-01-2004
			HK 1034156 A1	06-02-2004
			JP 2002506327 T	26-02-2002
			JP 2002506328 T	26-02-2002
			WO 9945700 A1	10-09-1999
			WO 9945702 A1	10-09-1999
			US 2003110499 A1	12-06-2003

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 01 30 4469

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

21-07-2004

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 0665551 A	02-08-1995	JP 7037369 A	07-02-1995
		DE 69428671 D1	22-11-2001
		DE 69428671 T2	08-08-2002
		EP 0665551 A1	02-08-1995
		US 6301427 B1	09-10-2001
		US 6035091 A	07-03-2000
		WO 9503610 A1	02-02-1995

EPO FORM P0439

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82